Performance Line UTV 300 / UTV 380





The ØVERAASEN UTV 300/UTV 380 Performance Line is a flexible unit snow blower designed for use on airports and roads. Based on the dual stage system, which consist of the slowly rotating horizontal auger and the fast turning impeller, the snow blower is capable of clearing all types of snow, even wet, hard packed or icy snow. The UTV 300/UTV 380 Perfomance Line has mechanical driveline and both the auger and the impeller are protected against damages by mechanical shear-pins. The snowblower is perfectly suited used in combination with 14-18 tons front end loaders.









eagle-myslik.com team-eagle.com





Performance Line UTV 300 / UTV 380



// STANDARD DELIVERY

- Control panel in cabin
- Volvo type quick coupler
- Rear skis
- 2 pcs. LED working lights
 Turnable impeller housing 45° left, 0° right
- Adjustable front skis





// TECHNICAL DATA	UTV 300	UTV 380
Diesel engine	MTU 6R1000 EU Stage V / Tier 4	MTU 6R1000 EU Stage V / Tier 4
Power output	230 kW / 312 HP	280 kW / 380 HP
Capacity	2 000 tons/h / 2 200 US tons	2 800 tons/h / 3 080 US tons/h
Casting distance, max	25 - 30 m / 95 - 115 ft	25 - 30 m / 95 - 115 ft
Clearing width	2 700mm / 8 ft 10 inch	2 990 mm / 9 ft 10 inch
Clearing height	1 300 mm / 4 ft 3 inch	1 370 mm / 4 ft 6 inch
Auger diameter	Ø 900 mm / 35 inch	Ø 900 mm / 35 inch
Impeller diameter	Ø 1 170 mm / 46 inch	Ø 1 300 mm / 51 inch
Weight	5 750 kg / 12 677 lb	5 950 kg / 13 117 lb
OPTIONS		
Extension of impeller housing's outlet		LED warning lights R+L in front (orange)
Extension of impeller housing's outlet with hydr. adjustable forward flap		Heated glass for LED working lights
Hydraulic slewing ring, 220°		Suitcase with brackets and tools
Chute with hydr. adjustable flap		Poly cutting edge (instead of steel)
Telescopic loading chute with hydr. adjustable flap (only UTV 300)		Drum protection, right and left side
2 pcs LED working lights on loading chute		Extra double working lights, LED
Engine heater, 220 Volt / 110 V		Extra panel with bracket
Battery charger, 220 Volt / 110 V		Extra set of cable with wall connectors
NATO socket, 24 Volt		Modifying kit for Z-link wheel loaders
NATO jumper cable with connectors, 5 m / 17 ft		Tilt blocking device
Wheels for blower head (pair)		Anticorrosion treatment
Sidowalk guida		

Sidewalk guide

Eagle & Myslik Inc. 2869 South Shoshone Englewood, CO, 80110 Ph: 1-855-835-7171 Team Eagle Ltd. 10 Trent Drive, PO Box 670 Campbellford, Ontario, K0L 1L0 Ph: 1-866-241-3264